



Qingdao Haiju industrial Co.,Ltd

ADD: No. 6 Hongkong Middle Road, Qingdao, China

TEL: 0086-13791935285 FAX:0086-532-8391153

Web:www.qdhaiju.en.alibaba.com Email:sale@qdhaiju.com

Electric Forklift Specification

Item			CPD750	CPD10F	CPD10	CPD16	CPD18	CPD20F	CPD20	CPD25	CPD30	CPD35
Power type			battery	battery	battery	battery	battery	battery	battery	battery	battery	battery
Rated load		KG	750	1000	1000	1600	1800	2000	2000	2500	3000	3500
load center		mm	300	400	500	500	500	500	500	500	500	500
Operation			Sit down	Sit down	Sit down	Sit down	Sit down	Sit down	Sit down	Sit down	Sit down	Sit down
Length	with pallet fork L1	mm	2040	2550	3170	3170	3120	3120	3380	3380	3630	3630
	without pallet fork L2		1400	1630	2100	2100	2050	2050	2310	2310	2560	2560
Width B			800	800	900	900	1050	1050	1150	1150	1220	1220
Hight	not raise portal H1		1680	2050	1950	1950	2000	2000	2000	2000	2080	2080
	overhead guard H2		1850	1850	1890	1890	2000	2000	2145	2145	2215	2215
	Working max H3		3070	3570	3655	3655	3800	3850	3995	3995	4185	4185
Distance from seat surface to top shield L3			970	970	970	970	1020	1020	1020	1020	1060	1060
Axle Distance L4			860	1080	1180	1180	1400	1400	1515	1515	1680	1680
Front overhang Y			300	300	340	340	320	320	483	483	490	490
Rear overhang L5			290	250	490	490	330	330	400	400	425	425
front track length R			700	700	955	955	880	880	970	970	1000	1000
rear track length P			668	668	890	890	830	830	950	950	980	980
Ground clearance F			90	90	90	90	100	100	135	135	145	145
maximum height of lift H			2500	3000	3000	3000	3000	3000	3000	3000	3000	3000
Free lift height H4			80	80	80	80	80	80	170	170	160	160
Fork spread S		703/190	703/190	765/180	765/180	925/200	1020/240	1024/200	1024/200	1060/250	1060/250	
minimum turning radius (outside) WA		1200	1800	1500	1950	1950	1950	2050	2200	2200	2200	
Min. right angle aisle width RA		1600	2000	2000	2000	3400	3400	3760	3760	4100	4100	

Mast tilt angle (front/rear) a/β	(°)	6°/12°	6°/12°	6°/12°	6°/12°	6°/12°	6°/12°	6°/12°	6°/12°	6°/12°	6°/12°
Maximum lift speed without load	mm/s	400	250	300	300	350	350	400	380	450	425
Maximum load rise speed		350	220	260	260	300	300	300	280	280	260
No-load maximum running speed	Km/h	13	12	15	15	17	17	15	15	14	14
No-load maximum running speed		12	11	14	14	14	14	14	14	14	12.5
Gradeability	%	≤10	≤10	≤10	≤10	≤10	≤15	≤15	≤15	≤15	≤15
standard forklift weight	Kg	1100	1580	2000	2200	3050	3600	4050	4200	5250	5400
Tire×=Drive wheel (F/R)		2x/2	2x/2	2x/2	2x/2	2x/2	2x/2	2x/2	2x/2	2x/2	2x/2
Tire Type (F/R)		solid	solid	solid	solid	solid	solid	solid	solid	solid	solid
Tire size (front)		15x4 1/2-8	15x4 1/2-8	16x6-8	18x7-8	18*7 1/2-10	18*7 1/2-10	7.00-12	7.00-12	28X9-15	28X9-15
Tire size (rear)		3.50-5	3.50-5	15x4 1/2-8	16x6-8	18*6-8	18*6-8	18x7-8	18x7-8	18x7-8	18x7-8
Brakes		hydraulic pressure-footstep	hydraulic pressure-footstep	hydraulic pressure-footstep	hydraulic pressure-footstep	hydraulic pressure-footstep	hydraulic pressure-footstep	hydraulic pressure-footstep	hydraulic pressure-footstep	hydraulic pressure-footstep	hydraulic pressure-footstep
parking brake		Mechanical manual type	Mechanical manual type	Mechanical manual type	Mechanical manual type	Mechanical manual type	Mechanical manual type	Mechanical manual type	Mechanical manual type	Mechanical manual type	Mechanical manual type
controller		Famous brand	Famous brand	Famous brand	Famous brand	Famous brand	Famous brand	Famous brand	Famous brand	Famous brand	Famous brand
Battery voltage/volume	V/Ah	48/140	48/160	48/240	48/240	48/350	48/400	48/500	48/500	80/500	80/500
Driving Motor Power	Kw	3.0AC	AC3	4.0AC	4.0AC	6AC	7.5AC	11.0AC	11.0AC	16.6AC	16.6AC
Pump motor power		3.0DC	DC3	5.5DC	5.5DC	10AC	12.0AC	12.0AC	12.0AC	12AC	12AC

Mark,Custom function,

- 1.Add mast to increase the lifting height.
- 2.Add Cylinder.
3. side shifter.
- 4.Add Ergonomic seat.
- 5.Add Environmentally friendly tyre.

Company brief introduction,

Qingdao Haiju industrial Co.,Ltd is a professional manufacturer of forklifts, electric forklift. Our company have complete and scientific quality management system. We are by integrity, strength and superior quality of products recognized by the industry. We have advanced plant production equipment, testing equipment, is and commitment to the new high-tech environmental protection technology enterprises, the main products: 0.5-3.5 tons of battery electric forklift, 1.0-3.5 tons of articulated narrow roadway forklift, 0.5-3.5 tons of electric Loaders and special non-standard forklifts and loaders to develop, the products are widely used in factories, warehousing, logistics, supermarkets, cold storage and other different occasions, it could be flexible in the narrow space channel operations, with easy operation, no noise, Beautiful appearance, low operating costs and other advantages. so we are doing our best to custom to reach different customer demand. Looking forward to making the long term cooperation with you by our company idea "superior quality, good service, competitive price".

Company workshop plant pictures,







